


Features

- Advanced shielded-gate trench technology
- High speed power switching
- RoHS compliant with Halogen-free

HF

Mechanical Data

- Case: PDFN5×6-8L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



PDFN5×6-8L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL038N08TH-5DL8	PDFN5×6-8L	5000 pcs / Tape & Reel	038N08TH

Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DS}	80	V
Gate-to-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ($T_C = 25^\circ\text{C}$, Silicon Limited)	I_D	120	A
Continuous Drain Current ($T_C = 25^\circ\text{C}$, Package Limited)		100	
Continuous Drain Current ($T_C = 100^\circ\text{C}$)		76	
Pulsed Drain Current ($t_p=10\mu\text{s}$, $T_C = 25^\circ\text{C}$)	I_{DM}	400	A
Single Pulse Avalanche Energy ^{*3}	E_{AS}	400	mJ
Power Dissipation ($T_C = 25^\circ\text{C}$)	P_D	114	W
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	-	-	1.1	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Air ^{*1}	$R_{\theta JA}$	-	-	55	$^\circ\text{C/W}$

Electrical Characteristics (@ $T_J = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	80	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 80V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = 10V, I _D = 20A	-	3.4	3.8	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	2	3	4	V
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	4050	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 40V	-	569	-	
C _{RSS}	Reverse Transfer Capacitance	f = 1.0MHz	-	26	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time *4	V _{DD} = 40V	-	25	-	ns
t _r	Turn-on Rise Time *4	V _{GS} = 10V	-	55	-	
t _{d(OFF)}	Turn-Off Delay Time *4	R _G = 10Ω	-	75	-	
t _f	Turn-Off Fall Time *4	I _D = 20A	-	52	-	
Q _G	Total Gate-Charge	V _{DD} = 40V	-	64	-	nC
Q _{GS}	Gate to Source Charge	V _{GS} = 10V	-	19	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 25A	-	13	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _S = 20A, V _{GS} = 0V	-	0.8	1.2	V
t _{rr}	Reverse Recovery Time	I _S = 20A, V _{GS} = 0V	-	64	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt = 100A/μs	-	115	-	nC

Notes:

1. The data tested by surface mounted on FR4 board, $t \leq 10$ sec
2. The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
3. The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 50V, V_{GS} = 10V, L = 0.5mH$
4. Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Output Characteristics




Fig 2 On-Resistance vs. Drain Current and Gate Voltage




Fig 3 On-Resistance vs. Gate-Source Voltage




Fig 4 Body-Diode Characteristics




Fig 5 On-Resistance vs. Junction Temperature




Fig 6 Transfer Characteristics




Fig 7 Capacitance Characteristics




Fig 8 Gate-Charge Characteristics




Fig 9 Normalized $V_{GS(th)}$ vs. Junction Temperature





Fig 10 Maximum transient thermal impedance

Package Outline Dimensions (Unit: mm)



PDFN5×6-8L		
Dimension	Min.	Max.
A	4.824	4.976
B	5.674	5.826
C	0.900	1.000
D	0.350	0.450
E	0.559	0.711
F	0.574	0.726
G	1.250	1.290
H	0.424	0.576
I	1.190	1.390
J	0.154	0.354
K	5.974	6.126
L	4.944	5.096
M	3.910	4.110
N	3.375	3.575

Mounting Pad Layout (Unit: mm)

PDFN5×6-8L

