


Features

- Advanced shielded-gate technology
- Ultra low $R_{DS(ON)}$ to minimize conduction losses
- Superior thermal resistance
- HBM: JESD22-A114-B: 1C

Mechanical Data

- Case: PDFN5×6-8L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

HF



PDFN5×6-8L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BLS012N04TH-5DL8	PDFN5×6-8L	5000 pcs / Tape & Reel	012N04TH

Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DSS}	40	V
Gate-to-Source Voltage	V_{GSS}	± 20	V
Continuous Drain Current ($T_C = 25^\circ\text{C}$, Silicon limited) ^{*1}	I_D	270	A
Continuous Drain Current ($T_C = 100^\circ\text{C}$, Silicon limited) ^{*1}		190	A
Continuous Drain Current ($T_A = 25^\circ\text{C}$) ^{*2}		43	A
Continuous Drain Current ($T_A = 100^\circ\text{C}$) ^{*2}		30	A
Pulsed Drain Current ($t_p = 10\mu\text{s}$, $T_C = 25^\circ\text{C}$) ^{*1}	I_{DM}	1080	A
Single Pulse Avalanche Energy ^{*3}	E_{AS}	500	mJ
Power Dissipation ($T_C = 25^\circ\text{C}$)	P_D	150	W
Power Dissipation ($T_A = 25^\circ\text{C}$) ^{*2}		3.8	W
Operating Junction Temperature Range	T_J	$-55 \sim +175$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +175$	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	-	0.8	1	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Air ^{*2}	$R_{\theta JA}$	-	34	40	$^\circ\text{C/W}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 1mA	40	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 40V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *4	V _{GS} = 10V,I _D = 75A	-	0.95	1.2	mΩ
		V _{GS} = 7V,I _D = 75A	-	1.2	1.6	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	2	3	4	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	4.9	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	5593	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 25V	-	1652	-	
C _{RSS}	Reverse Transfer Capacitance	f = 300KHz	-	7	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time	V _{DD} = 30V	-	25	-	ns
t _r	Turn-on Rise Time	V _{GS} = 15V	-	95	-	
t _{d(OFF)}	Turn-Off Delay Time	R _G = 3.3Ω	-	145	-	
t _f	Turn-Off Fall Time	I _D = 40A	-	109	-	
Q _G	Total Gate-Charge	V _{DD} = 32V	-	67	-	nC
Q _{GS}	Gate to Source Charge	V _{GS} = 10V	-	24	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 75A	-	7	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *4	I _S = 75A, V _{GS} = 0V	-	0.83	1.2	V
t _{rr}	Reverse Recovery Time	I _S = 40A, V _{GS} = 0V	-	130	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt = 100A/μs	-	215	-	nC

Notes:

- The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted. De-rating will be required based on the actual environmental conditions
- The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 30V, V_{GS} = 10V, L = 0.5mH$
- The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature







Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature




Package Outline Dimensions (Unit: mm)



PDFN5×6-8L		
Dimension	Min.	Max.
A	4.824	4.976
B	5.674	5.826
C	0.900	1.000
D	0.350	0.450
E	0.559	0.711
F	0.574	0.726
G	1.250	1.290
H	0.424	0.576
I	1.190	1.390
J	0.154	0.354
K	5.974	6.126
L	4.944	5.096
M	3.910	4.110
N	3.375	3.575

Mounting Pad Layout (Unit: mm)

PDFN5×6-8L



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.