



Features

- ESD / transient protection of high speed data lines
 - IEC 61000-4-2 (ESD): ± 30 kV (air), ± 30 kV (contact)
- Working voltage: $V_{RWM} = 5V$
- Low leakage current
- Very low load capacitance

HF



DFN0603-2L

Mechanical Data

- Case: DFN0603-2L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
GESD5V0B2LP3	DFN0603-2L	10000 pcs / Tape & Reel	N

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
IEC 61000-4-2; ESD (Air)	V_{ESD-A}	± 30	kV
IEC 61000-4-2; ESD (Contact)	V_{ESD-C}	± 30	kV
Peak Pulse Power ($t_p = 8/20\mu\text{s}$)	P_{PP}	70	W
Peak Pulse Current ($t_p = 8/20\mu\text{s}$)	I_{PP}	8	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	0.25	W
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	400	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Lead	$R_{\theta JL}$	204	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	240	$^\circ\text{C/W}$
Junction Temperature	T_J	$-55 \sim +125$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Stand-off Voltage	V_{RWM}		-	-	5	V
Reverse Breakdown Voltage	$V_{(BR)}$	$I_T = 1\text{mA}$	6	-	8	V
Reverse Leakage Current	I_R	$V_{RWM} = 5\text{V}$	-	-	100	nA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$, $t_p = 8/20\mu\text{s}$	-	-	8.5	V
		$I_{PP} = 7\text{A}$, $t_p = 8/20\mu\text{s}$	-	-	12.0	V
		$I_{PP} = 8\text{A}$, $t_p = 8/20\mu\text{s}$	-	-	14.0	V
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$	-	15	18	pF

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 8/20 μs waveform per IEC61000-4-5




Fig 2 ESD pulse waveform according to IEC61000-4-2




Fig 3 Power Derating Curve




Fig 4 Clamping Voltage vs. Peak Pulse Current





Fig 5 TLP Measurement

Package Outline Dimensions (Unit: mm)


DFN0603-2L



DFN0603-2L			
Dim	Min	Typ	Max
A	0.595	0.620	0.645
B	0.270	0.300	0.350
C	0.295	0.320	0.345
D	0.190	0.240	0.290
E	0.140	0.190	0.240
F	-	0.355	-
H	0	0.020	0.030

Package Outline Dimensions (Unit: mm)

DFN0603-2L



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.