

SCHOTTKY BARRIER RECTIFIER

Reverse Voltage: 200 V
Forward Current: 2.0 A


FEATURES

- Metal-Semiconductor junction with guard ring
- Epitaxial construction
- Low forward voltage drop, low switching losses
- High surge capacity
- For use in low voltage, high frequency inverters free wheeling, and polarity protection applications

MECHANICAL DATA

- **Case:** JEDEC DO-15, molded plastic body
- **Terminals:** Axial lead, solderable per MIL-STD-750, Method 2026
- **Polarity:** As marked
- **Mounting Position:** Any

DO-15



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 50Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbol	SB2200	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	200	V
Maximum RMS voltage	V_{RWS}	140	V
Maximum DC blocking voltage	V_{DC}	200	V
Maximum average forward total device rectified current @ $T_L=110^\circ\text{C}$	$I_{(AV)}$	2.0	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	50	A
Maximum instantaneous forward voltage @ 2.0A	V_F	0.95	V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	I_R	0.1 10	mA
Maximum thermal resistance (Note1)	$R_{\theta JA}$	50	$^\circ\text{C/W}$
Operating junction temperature range	T_J	-55 --- +150	$^\circ\text{C}$
Storage temperature range	T_{STG}	-55 --- +150	$^\circ\text{C}$

NOTES: 1. Thermal resistance from junction to ambient.

www.galaxycn.com

FIG.1 TYPICAL FORWARD CHARACTERISTICS




FIG.2 FORWARD DERATING CURVE




FIG.3 TYPICAL REVERSE CHARACTERISTICS




FIG.4 PEAK FORWARD SURGE CURRENT

